

SHELVING ACCESSORIES




Shelf Ledges

- Keeps items from falling off shelves
- Ledges mount to posts and can be used with all ISS shelves
- Height 6 in.
- Ledges can be stacked on top of each other for additional height

Model No.*	Fits Shelf Width or Length	Weight (lbs.)
LU14	14	1/2
LU18	18	1/2
LU21	21	3/4
LU24	24	1
LU30	30	1 ½
LU36	36	1 ½
LU42	42	2
LU48	48	2
LU54	54	2 ¼
LU60	60	2 ½
LU72	72	3

* Select a finish by adding a suffix to the model number.

Finish	Suffix
Plating Plus™	C
Grey Bond®	E
Gold Bond®	Y



Side & Back Ledges

Clamps, Clips & Foot Plates



Post Clamps
PC2



Modified Foot Plate
MFP1C



Half Modified Foot Plate
MMP1C

Model No.	Part	Description
PC2	Post Clamps	Joins 2 Posts Side-By-Side
MFP1*	Modified Foot Plate	May Be Bolted To Floor
MMFP1*	Half Modified Foot Plate	May Be Bolted To Floor

* Select a finish by adding a suffix to the model number.



Shelf Dividers

Shelf Dividers

- Maintain separation of goods with shelf dividers
- Height 8"

Model No.*	Length (in.)	Fits Shelf Width (in.)	Fits Shelf Width (mm)	Weight (lbs.)	Weight (Kg.)
SDU14	13 ¼	14	356	¾	0.3
SDU18	17 ¼	18	457	1	0.4
SDU21	20 ¼	21	533	1	0.4
SDU24	23 ¼	24	610	1 ¼	0.5

* Select a finish by adding a suffix to the model number.

Stem Casters

- Use stem casters to add mobility and increase efficiency
- Stem casters are load rated for 75 to 300 lbs.
- Three caster styles available: swivel only, swivel with brake, and rigid
- The forks of all stem casters are plated steel except for models CM6PS and CM6PSB which are stainless steel
- Three types of tire treads available: Resilient Rubber, Polyurethane, and Conductive Rubber

- Resilient casters are great for use on rough flooring as they are long lasting, quiet and inexpensive
- Polyurethane casters are non-marking and prevent undue wear on carpets and floors. They are suited to demanding environments such as extreme temperatures and the presence of solvents or organic chemicals
- Conductive casters are designed for dissipation of static charge build-up in computer, electronic or medical applications



Swivel Caster



Swivel Caster with brake

Swivel Model No.	Swivel w/Brake Model No.	Rigid Model No.	Dia. (in.)	Dia. (mm)	Face (in.)	Face (mm)	Load Rating (lbs.)	Load Rating (Kg.)	Wheel Material	Weight (lbs.)	Weight (Kg.)
CM5M	CM5MB	CM5MR*	5	127	1 ¼	32	200	91	Resilient Rubber	2 ¾	1.2
CM5P	CM5PB	CM5PR*	5	127	1 ¼	32	300	136	Polyurethane	3	1.4
CM3M	CM3MB	—	3	76	1 ¼	32	150	68	Resilient Rubber	1 ½	0.7
CM5MC**	CM5MCB**	—	5	127	1 ¼	32	200	91	Conductive Rubber	2 ¾	1.2
CM6PS	CM6PSB	—	6	152	1 ¼	32	300	136	Polyurethane	3	1.4

* Caster channel required. Order separately. ** Conductive surelocks required. Ordered separately.

For SPG's complete product menu, visit www.spgusa.com or call 877.503.4SPG (4774)

